

Frequency Range	617-894 1695-2400
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2° - 12°x2

Type QUA8-1LX1HX-BW65


Base Station Antenna

4-ports 617-894 /1695-2400 MHz 65°, 16 / 18 dBi, 2°-12° / 2°-12° Tilt Antenna With 2 Integrated RCUs.



Electrical Specifications

Frequency Range(MHz)		617-894			1695-2400		
		617-698	698-824	824-894	1695-1920	1920-2180	2300-2400
Polarization		±45°					
Horizontal 3dB Beamwidth(°)		70	65	60	66	63	58
Vertical 3dB Beamwidth(°)		10.4	9.1	8.0	5.5	5	4.3
Gain (dBi)		15.1	15.6	16.0	17.6	18.0	18.1
Electrical Downtilt		2°-12°			2°-12°		
Upper Sidelobe Suppression(dB)	First	≥16	≥16	≥16	≥16	≥16	≥16
Front-to-Back Ratio Total Power, ± 30° (dB)		≥25	≥25	≥25	≥25	≥25	≥25
Cross polar ratio	Main direction(dB)	≥16	≥16	≥16	≥16	≥16	≥16
	± 60° (dB)	≥7	≥7	≥7	≥7	≥7	≥7
Isolation ports		≥25 dB					
Isolation Frequency		≥30 dB					
VSWR		< 1.5					
Intermodulation IM3		< -150 dBc(2x43dBm carrier)					
Impedance		50 Ω					
Max. Power per Input (at 50°C ambient temperature)		500 W			300 W		
Lightning Protection		DC Ground					



Mechanical Specifications

Radome Material	Fiberglass
Connector Type and Location	4.3-10x4 ,Bottom iRCU in:1 x 8 pin male iRCU out:1 x 8 pin female
Dimensions,HxWxD(mm)/(inches)	2438 x 355 x 165 / 95.9 x 14.0x 6.5
Packing Size(mm)/(inches)	2710 x 460 x 275 / 106.7 x 18.1 x 10.8
Weight ,w/o Mounting kit(kg)/(lbs)	29 / 63.8
Weight with Downtilt Bracket(kg)/(lbs)	36 / 79.2
Weight with Fixed Bracket(kg)/(lbs)	34 / 74.8
Packing Weight (with Downtilt Bracket) (kg)/(lbs)	42 / 92.4
Packing Weight (with Fixed Bracket) (kg)/(lbs)	40 / 88
Max. Wind Velocity(mph)	150
Mounting hardware	Φ 50 mm ~ Φ 115 mm
Operational Temperature(°C)	-40 to +65
Operational Humidity(%)	<95
Wind Load at 100mph (Frontal/lateral/Rearside(N))	1001/271/723

This publication is issued to information only and is not to form part of any order or contract DENGYO reserves the right to changes specifications without prior notice.


Type QUA8-1LX1HX-BW65

Frequency Range	617-894 1695-2400
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2° - 12°x2

Integrated RET Properties


RET Type	2x Type 1 Single RET	
Protocols	Compliant to AISG 2.0/3GPP	
Input voltage range	+10~+30VDC(pin 6)	
Power consumption	<2W(stand by);<13W(motor activated)	
Connectors	AISG	2 x 8 pin connector acc. To IEC 60130-9 Acc.to AISG Daisy chain in:male Daisy chain out:female
	Antenna	Two motor shaft(Embedded motor)
Hardware interface	AISG	RS485A/B(pin5/pin3);Power supply(pin6); DC return(pin7)Acc.to AISG
Adjustment time(full range)	40 sec(typically,depending on antenna)	
Adjustment Cycles	≥10000	
Torque Max	≥160mN.m	
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile,8/20 μs 10 Repetitions Min.@ 6kA IEC 61312-1 Annex B Current Pulse Profile, 10/350 μs,200 Repetitions Min. @ 0.6kA	

COMPREHENSIVE TILT CONFIGURATION



Frequency Range	Array	RET Unique ID
617-894MHz	R1	NDPMXXXXXXXX-6089R1
1695-2400MHz	Y1	NDPMXXXXXXXX-1724Y1


Note: (1) Physical RET Unit containing (2) Single RET




Frequency Range	617-894 1695-2400
Polarization	$\pm 45^\circ$
Half-Power Beam Width	65°
Electrical Downtilt	2° - 12°x2

Type QUA8-1LX1HX-BW65

Radiation Pattern (617 - 824 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Patterns (824 - 894 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Pattern (1695 - 1920 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Patterns (1920 - 2180 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Pattern (2180 - 2400 MHz)



Horizontal Pattern



Vertical Pattern