

Frequency Range	617-894x2
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x2

Type QUA4-2A-RB45

Base Station Antenna

4-ports 617-894 / 617-894 MHz 45°, 14.5/ 14.5 dBi, 2°-12° / 2°-12°Tilt Antenna With 2 Integrated RCUs.



Electrical Specifications

Frequency Range(MHz)		2x617-894		
		617-698	698-824	824-894
Polarization		±45°		
Horizontal 3dB Beamwidth(°)		50	46	42
Vertical 3dB Beamwidth(°)		19	16.5	14.5
Gain (dBi)		13.3	13.8	14.3
Electrical Downtilt		2°-12°		
Upper Sidelobe Suppression(dB)	First	≥16	≥16	≥16
Front-to-Back Ratio Total Power,±30° (dB)		≥22	≥23	≥24
Cross polar ratio	Main direction(dB)	≥17	≥17	≥17
	±30° (dB)	≥7	≥7	≥7
Isolation ports		≥25 dB		
Isolation Frequency		≥30 dB		
VSWR		< 1.5		
Intermodulation IM3		< -153 dBc(2x43dBm carrier)		
Impedance		50 Ω		
Max. Power per Input (at 50°C ambient temperature)		500 W		
Lightning Protection		DC Ground		



Mechanical Specifications

Radome Material	Fiberglass
Connector Type and Location	4.3-10x4 ,Bottom iRCU in:1 x 8 pin male iRCU out:1 x 8 pin female
Dimensions,HxWxD(mm)/(inches)	1300 x 499 x 180 / 51.2 x 19.6 x 7.1
Packing Size(mm)/(inches)	1600 x 620 x 325 / 63.0 x 24.4 x 12.8
Weight ,w/o Mounting kit(kg)/(lbs)	25 / 55
Weight w/ Downtilt Bracket(kg)/(lbs)	32 / 70.4
Weight w/ Fixed Bracket(kg)/(lbs)	30/ 66
Packing Weight (w/ Downtilt Bracket) (kg)/(lbs)	38/ 83.6
Packing Weight (w/ Fixed Bracket) (kg)/(lbs)	36 / 79.2
Max. Wind Velocity(mph)	150
Mounting hardware	Φ 50 mm ~ Φ 115 mm
Operational Temperature(°C)	-40 to +65
Operational Humidity(%)	<95
Wind Load at 100mph (Frontal/lateral/Rearside(N))	755/149/544


Type QUA4-2A-RB45

Frequency Range	617-894x2
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x2

Integrated RET Properties


RET Type	2x Type 1 Single RET	
Protocols	Compliant to AISG 2.0/3GPP	
Input voltage range	+10~+30VDC(pin 6)	
Power consumption	<2W(stand by);<13W(motor activated)	
Connectors	AISG	2 x 8 pin connector acc. To IEC 60130-9 Acc.to AISG Daisy chain in:male Daisy chain out:female
	Antenna	Two motor shaft(Embedded motor)
Hardware interface	AISG	RS485A/B(pin5/pin3);Power supply(pin6); DC return(pin7)Acc.to AISG
Adjustment time(full range)	40 sec(typically,depending on antenna)	
Adjustment Cycles	≥10000	
Torque Max	≥160mN.m	
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile,8/20 μs 10 Repetitions Min.@ 6kA IEC 61312-1 Annex B Current Pulse Profile, 10/350 μs,200 Repetitions Min. @ 0.6kA	

COMPREHENSIVE TILT CONFIGURATION



Frequency Range	Array	RET Unique ID
617-894MHz	R1	NDPMXXXXXXXX-6089R1
617-894MHz	R2	NDPMXXXXXXXX-6089R2


Note: (1) Physical RET Unit
containing (2) Single RET




Frequency Range	617-894x2
Polarization	$\pm 45^\circ$
Half-Power Beam Width	45°
Electrical Downtilt	$2^\circ - 12^\circ \times 2$

Type QUA4-2A-RB45

Radiation Pattern (617 - 824 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Patterns (824 - 894 MHz)



Horizontal Pattern



Vertical Pattern