

Frequency Range	617-894x2 1695-2200x2
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2° - 14°x2 2° - 12°x2

Type OCT4-2A2K-RB65

Base Station Antenna

8-ports 617-894 / 617-894 /1695-2200 /1695-2200 MHz 65°, 13.5 / 13.5/ 17 / 17 dBi, 2°-14° / 2°-14° / 2°-12° / 2°-12° Tilt Antenna With 2 Integrated RCUs.

Electrical Specifications



Frequency Range(MHz)		2x617-894			2x1695-2200		
		617-698	698-824	824-894	1695-1880	1850-1990	1920-2200
Polarization		±45°					
Horizontal 3dB Beamwidth(°) ¹		68±5	64±5	60±5	66±4	65±4	63±4
Vertical 3dB Beamwidth(°) ¹		19.0±1.0	16.5±1.0	14.5±1.0	8.1±0.5	7.5±0.5	7.0±0.5
Gain over all tilts ,max,(dBi)		12.1	12.8	13.3	16.6	17.0	17.2
Average gain over all tilts,dBi		11.5±0.6	12.2±0.6	12.7±0.6	16.2±0.4	16.6±0.4	16.8±0.4
Electrical Downtilt		2°-14°			2°-12°		
Upper Sidelobe Suppression(dB) ¹	First	≥16	≥16	≥16	≥19	≥19	≥19
	Boresight to 20° ¹	≥16	≥16	≥16	≥16	≥16	≥16
Front-to-Back Ratio Co-polar power (dB)	@180°	≥26	≥27	≥27	≥30	≥30	≥30
	@180±30°	≥25	≥25	≥25	≥26	≥26	≥26
Cross polar ratio	Main direction(dB)	≥20	≥20	≥20	≥20	≥20	≥20
	±60° (dB)	≥7	≥7	≥7	≥7	≥7	≥7
Minimum cross-polar isolation, port-to-port, dB ¹		≥25dB					
Isolation Frequency		≥30dB					
VSWR		< 1.5					
Intermodulation IM3		< -153 dBc(2x43dBm carrier)					
Impedance		50 Ω					
Max. Power per Input (at 50°C ambient temperature)		500 W			300 W		
Lightning Protection		DC Ground					

¹Typical value over frequency and tilt

Mechanical Specifications

Radome Material	ASA
Connector Type and Location	4.3-10x8 ,Bottom iRCU in:1 x 8 pin male iRCU out:1 x 8 pin female
Dimensions,HxWxD(mm)/(inches)	1220 x 499 x 180 / 48.0 x 19.6x 7.1
Packing Size(mm)/(inches)	1585 x 560 x 300 / 62.4 x 22.0 x 11.8
Weight ,w/o Mounting kit(kg)/(lbs)	26 / 57.2
Weight w/ Downtilt Bracket(kg)/(lbs)	33 / 72.6
Weight,w/ Fixed Bracket (kg)/(lbs)	31 / 68.2
Packing Weight (w/ Downtilt Bracket) (kg)/(lbs)	42 / 92.4
Packing Weight (w/ Fixed Bracket) (kg)/(lbs)	40 / 88
Max. Wind Velocity(mph)	150
Mounting hardware	⌀ 50 mm ~ ⌀ 115 mm
Operational Temperature(°C)	-40 to +65
Operational Humidity(%)	<95
Wind Load at 100mph (Frontal/lateral/Rearside(N))	992/222/717

This publication is issued to information only and is not to form part of any order or contract DENGYO reserves the right to changes specifications without prior notice.


Type OCT4-2A2K-RB65

Frequency Range	617-894x2 1695-2200x2
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2° - 14°x2 2° - 12°x2

Integrated RET Properties


RET Type	2x Type 1 Single RET	
Protocols	Compliant to AISG 2.0/3GPP	
Input voltage range	+10~+30VDC(pin 6)	
Power consumption	<2W(stand by);<13W(motor activated)	
Connectors	AISG	2 x 8 pin connector acc. To IEC 60130-9 Acc.to AISG Daisy chain in:male Daisy chain out:female
	Antenna	Two motor shaft(Embedded motor)
Hardware interface	AISG	RS485A/B(pin5/pin3);Power supply(pin6); DC return(pin7)Acc.to AISG
Adjustment time(full range)	40 sec(typically,depending on antenna)	
Adjustment Cycles	≥10000	
Torque Max	≥160mN.m	
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile,8/20 μs 10 Repetitions Min.@ 6kA IEC 61312-1 Annex B Current Pulse Profile, 10/350 μs,200 Repetitions Min. @ 0.6kA	

COMPREHENSIVE TILT CONFIGURATION



Frequency Range	Array	RET Unique ID
617-894MHz	R1/R2	NDPMXXXXXXXX-6089R1
1695-2200MHz	B1/B2	NDPMXXXXXXXX-1722B1


Note: (1) Physical RET Unit containing (2) Single RET




Type OCT4-2A2K-RB65

Frequency Range	617-894x2 1695-2200x2
Polarization	$\pm 45^\circ$
Half-Power Beam Width	65°
Electrical Downtilt	$2^\circ - 14^\circ \times 2$ $2^\circ - 12^\circ \times 2$

Radiation Pattern (617 - 824 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Patterns (824 - 894 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Pattern (1695 - 1920 MHz)




Horizontal Pattern




Vertical Pattern

Radiation Patterns (1920 - 2200 MHz)



Horizontal Pattern



Vertical Pattern