

Frequency Range	617-894x2 1695-2400x4
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x6

Type DOD4-2LX4HX-BW45



Base Station Antenna

12-ports 617-894 / 617-894 /1695-2400 /1695-2400 /1695-2400 /1695-2400 MHz 45°, 14 / 14 / 18.1 / 18.1 / 18.1 / 18.1 dBi, 2°-12° / 2°-12° / 2°-12° / 2 - 12 ° / 2°-12° / 2 - 12 °Tilt Antenna With 4 Integrated RCUs.

Electrical Specifications

Frequency Range(MHz)		2x617-894			4x1695-2400		
		617-698	698-824	824-894	1695-1920	1920-2180	2300-2400
Polarization		±45°					
Horizontal 3dB Beamwidth(°)		50	46	42	48	45	41
Vertical 3dB Beamwidth(°)		19	16.5	14.5	7.5	6.5	6
Gain (dBi)		13	13.5	14	17.1	17.6	18.1
Electrical Downtilt		2°-12°			2°-12°		
Upper Sidelobe Suppression(dB)	First	≥16	≥16	≥16	≥16	≥16	≥16
Front-to-Back Ratio Total Power, ± 30° (dB)		≥25	≥25	≥25	≥25	≥25	≥25
Cross polar ratio	Main direction(dB)	≥17	≥17	≥17	≥17	≥17	≥17
Isolation ports		≥24 dB					
Isolation Frequency		≥30 dB					
VSWR		< 1.5					
Intermodulation IM3		< -150 dBc(2x43dBm carrier)					
Impedance		50 Ω					
Max. Power per Input (at 50°C ambient temperature)		500 W			300 W		
Lightning Protection		DC Ground					

Mechanical Specifications


Radome Material	ASA
Connector Type and Location	4.3-10x12 ,Bottom iRCU in:1 x 8 pin male iRCU out:1 x 8 pin female
Dimensions,HxWxD(mm)/(inches)	1300 x 533 x 160 / 51.2 x 21.0x 6.3
Packing Size(mm)/(inches)	1645 x 633 x 291 / 64.7x 24.9 x 11.4
Weight ,w/o Mounting kit(kg)/(lbs)	28 / 61.6
Weight w/ Downtilt Bracket(kg)/(lbs)	35 / 77
Weight w/ Fixed Bracket(kg)/(lbs)	33 / 72.6
Packing Weight (w/ Downtilt Bracket) (kg)/(lbs)	44 / 96.8
Packing Weight (w/ Fixed Bracket) (kg)/(lbs)	42 / 92.4
Max. Wind Velocity(mph)	150
Mounting hardware	Φ 50 mm ~ Φ 115 mm
Operational Temperature(°C)	-40 to +65
Operational Humidity(%)	<95
Wind Load at 100mph (Frontal/lateral/Rearside(N))	800/148/576

Frequency Range	617-894x2 1695-2400x4
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x6

Integrated RET Properties


RET Type	4x Type 1 Single RET	
Protocols	Compliant to AISG 2.0/3GPP	
Input voltage range	+10~+30VDC(pin 6)	
Power consumption	<2W(stand by);<13W(motor activated)	
Connectors	AISG	2 x 8 pin connector acc. To IEC 60130-9 Acc.to AISG Daisy chain in:male Daisy chain out:female
	Antenna	Two motor shaft(Embedded motor)
Hardware interface	AISG	RS485A/B(pin5/pin3);Power supply(pin6); DC return(pin7)Acc.to AISG
Adjustment time(full range)	40 sec(typically,depending on antenna)	
Adjustment Cycles	≥10000	
Torque Max	≥160mN.m	
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile,8/20 μs 10 Repetitions Min.@ 6kA IEC 61312-1 Annex B Current Pulse Profile, 10/350 μs,200 Repetitions Min. @ 0.6kA	

COMPREHENSIVE TILT CONFIGURATION



Frequency Range	Array	RET Unique ID
617-894MHz	R1	NDPMXXXXXXXX-6089R1
617-894MHz	R2	NDPMXXXXXXXX-6089R2
1695-2400MHz	Y1/Y3	NDPMXXXXXXXX-1724Y1
1695-2400MHz	Y2/Y4	NDPMXXXXXXXX-1724Y2





Note: (1) Physical RET Unit containing (4) Single RET





Frequency Range	617-894x2 1695-2400x4
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x6

Type DOD4-2LX4HX-BW45



This publication is issued to information only and is not to form part of any order or contract DENGYO reserves the right to changes specifications without prior notice.



Radiation Pattern (1695 - 1920 MHz)



Radiation Patterns (1920 - 2180 MHz)



Radiation Pattern (2300 - 2400 MHz)

