

Frequency Range	617-894x2 1695-2400x4
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x2 2° - 12°x4

Type DOD6-2LX4HX-BW45



Base Station Antenna

12-ports 617-894 / 617-894 /1695-2400 /1695-2400 /1695-2400 /1695-2400 MHz 45°, 15.5 / 15.5 / 18 / 18 / 18 / 18dBi, 2°-12° / 2°-12° / 2°-12° / 2 - 12° / 2°-12° / 2 - 12° Tilt Antenna With 4 Integrated RCUs.

Electrical Specifications

Frequency Range(MHz)		2x617-894			4x1695-2400		
		617-698	698-824	824-894	1695-1920	1920-2180	2300-2400
Polarization		±45°					
Horizontal 3dB Beamwidth(°)		50	46	42	48	45	41
Vertical 3dB Beamwidth(°)		13.5	12	10.5	7.5	6.5	6
Gain (dBi)		14.4	14.9	15.5	17.1	17.6	18.1
Electrical Downtilt		2°-12°			2°-12°		
Upper Sidelobe Suppression(dB)	First	≥16	≥16	≥16	≥16	≥16	≥16
Front-to-Back Ratio Total Power, ±30° (dB)		≥25	≥25	≥25	≥25	≥25	≥25
Cross polar ratio	Main direction(dB)	≥17	≥17	≥17	≥17	≥17	≥17
Isolation ports		≥25 dB					
Isolation Frequency		≥30 dB					
VSWR		< 1.5					
Intermodulation IM3		< -150 dBc(2x43dBm carrier)					
Impedance		50 Ω					
Max. Power per Input (at 50°C ambient temperature)		500 W			300 W		
Lightning Protection		DC Ground					

Mechanical Specifications

Radome Material	ASA
Connector Type and Location	4.3-10x12 ,Bottom iRCU in:1 x 8 pin male iRCU out:1 x 8 pin female
Dimensions,HxWxD(mm)/(inches)	1850 x 533 x 160 / 72.8 x 21.0x 6.3
Packing Size(mm)/(inches)	2195 x 633 x 291 / 86.4 x 24.9 x 11.4
Weight ,w/o Mounting kit(kg)/(lbs)	33.5 / 73.7
Weight w/ Downtilt Bracket(kg)/(lbs)	40.5 / 89.1
Weight w/ Fixed Bracket(kg)/(lbs)	38.5 / 84.7
Packing Weight (w/ Downtilt Bracket) (kg)/(lbs)	49.5 / 108.9
Packing Weight (w/ Fixed Bracket) (kg)/(lbs)	47.5 / 104.5
Max. Wind Velocity(mph)	150
Mounting hardware	ϕ 50 mm ~ ϕ 115 mm
Operational Temperature(°C)	-40 to +65
Operational Humidity(%)	<95
Wind Load at 100mph (Frontal/lateral/Rearside(N))	1138/211/819


Frequency Range	617-894x2 1695-2400x4
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x2 2° - 12°x4

Type DOD6-2LX4HX-BW45

Integrated RET Properties


RET Type	4x Type 1 Single RET	
Protocols	Compliant to AISG 2.0/3GPP	
Input voltage range	+10~+30VDC(pin 6)	
Power consumption	<2W(stand by); <13W(motor activated)	
Connectors	AISG	2 x 8 pin connector acc. To IEC 60130-9 Acc.to AISG Daisy chain in:male Daisy chain out:female
	Antenna	Two motor shaft(Embedded motor)
Hardware interface	AISG	RS485A/B(pin5/pin3);Power supply(pin6); DC return(pin7)Acc.to AISG
Adjustment time(full range)	40 sec(typically,depending on antenna)	
Adjustment Cycles	≥10000	
Torque Max	≥160mN.m	
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile,8/20 μs 10 Repetitions Min.@ 6kA IEC 61312-1 Annex B Current Pulse Profile, 10/350 μs,200 Repetitions Min. @ 0.6kA	

COMPREHENSIVE TILT CONFIGURATION



Frequency Range	Array	RET Unique ID
617-894MHz	R1	NDPMXXXXXXXX-6089R1
617-894MHz	R2	NDPMXXXXXXXX-6089R2
1695-2400MHz	Y1/Y3	NDPMXXXXXXXX-1727Y1
1695-2400MHz	Y2/Y4	NDPMXXXXXXXX-1727Y2


Note: (1) Physical RET Unit containing (4) Single RET



Frequency Range	617-894x2 1695-2400x4
Polarization	±45°
Half-Power Beam Width	45°
Electrical Downtilt	2° - 12°x2 2° - 12°x4

Type DOD6-2LX4HX-BW45


Radiation Pattern (617 - 824 MHz)



Horizontal Pattern

Vertical Pattern


Radiation Patterns (824 - 894 MHz)



Horizontal Pattern

Vertical Pattern


Radiation Pattern (1695 - 1920 MHz)



Horizontal Pattern

Vertical Pattern


Radiation Patterns (1920 - 2180 MHz)



Horizontal Pattern

Vertical Pattern

Radiation Pattern (2300 - 2400 MHz)



Horizontal Pattern

Vertical Pattern