


Frequency Range	617-894x2 1695-2690x2 3300-4200
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2°-12°x5

Type BMF6-2LX3HX-CB65

2 x617-894 /2 x1695-2690 /3300-4200 MHz 65°, 2 x15 / 2 x18 / 16 dBi, 2 x2°-12° / 2 x2°-12° / 2°-12°Tilt Antenna With 4 Integrated RCUs.

Electrical Specifications

General parameters	Frequency range (MHz)		3300-4200
	Polarization		±45
	Electrical downtilt(°)		2-12
	Electrical downtilt tolerance(°)		±1
Calibration and electrical parameters	Coupling factor between calibration port and each antenna port (dB)		-26±2
	Max.amplitude tolerance from calibration port to input ports(dB)		≤1.0
	Max.phase tolerance from calibration port to input ports(°)		≤10
	Ports VSWR		<1.5
	Avg. power per capacity (W)		40
	Co-polarization isolation between ports(dB)		≥20
	Cross-polarization isolation between ports(dB)		≥23
Radiation parameters	Single column Beam	Gain(dBi)	15.5
		Horizontal 3dB beam width(°)	65
		Vertical 3dB beam width(°)	6.5
		Cross polar ratio(dB, 0°)	≥16
		Front to back ratio(dB)	≥25
		Vertical sidelobe suppression for first sidelobe above main beam(dB)	≥15
	65° Broadcast beam	Gain(dBi)	15.5
		Horizontal 3dB beam width(°)	65
		Vertical 3dB beam width(°)	6.5
		Cross polar ratio(dB, 0°)	≥16
		Front to back ratio(dB)	≥25
		Vertical sidelobe suppression for first sidelobe above main beam(dB)	≥15
	Service beam	0°direct beam gain(dBi)	21
		0°direct beam horizontal 3dB beam width(°)	19
		0°direct beam front to back ratio(dB)	≥28
		0°direct beam cross polar ratio(axial)(dB)	≥17





Base Station Antennas

Type **BMF6-2LX3HX-CB65**

Frequency Range	617-894x2 1695-2690x2 3300-4200
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2°-12°x5

Frequency Range(MHz)		2x617-894			2x1695-2690			
		617-698	698-824	824-894	1695-1920	1920-2180	2300-2400	2490-2690
Polarization		±45°						
Horizontal 3dB Beamwidth(°)		71	65	60	66	63	58	60
Vertical 3dB Beamwidth(°)		14.5	12.5	11	7.5	6.5	6	5.5
Gain (dBi)		13.7	14.4	15	16.5	17.0	17.3	17.8
Electrical Downtilt		2°-12°			2°-12°			
Upper Sidelobe Suppression(dB)	First	≥16	≥16	≥16	≥16	≥16	≥16	≥16
Front-to-Back Ratio Total Power,± 30° (dB)		≥22	≥23	≥24	≥25	≥25	≥25	≥25
Cross polar ratio	Main direction(dB)	≥17	≥17	≥17	≥17	≥17	≥17	≥17
	± 60° (dB)	≥7	≥7	≥7	≥7	≥7	≥7	≥7
Isolation ports		≥25 dB						
Isolation Frequency		≥30 dB						
VSWR		< 1.5						
Intermodulation IM3		< -150 dBc(2x43dBm carrier)						
Impedance		50 Ω						
Max. Power per Input (at 50°C ambient temperature)		500 W			250 W			
Lightning Protection		DC Ground						

Mechanical Specifications

Radome Material	FiberGlass
Connector Type and Location	4.3-10 Female x8, Bottom 1xMQ5 Male+1 xMQ4 Male iRCU in:1 x 8 pin male iRCU out:1 x 8 pin female
Dimensions,HxWxD(mm)/(inches)	1850 x 499 x 180 / 72.8 x 19.6 x 7.1
Packing Size(mm)/(inches)	2195 x 599 x 311 / 86.4 x 23.6 x 12.2
Weight ,w/o Mounting kit(kg)/(lbs)	45 / 99
Weight with Downtilt Bracket(kg)/(lbs)	52 / 114.4
Weight with Fixed Bracket(kg)/(lbs)	50 / 110
Packing Weight (with Downtilt Bracket) (kg)/(lbs)	63 / 138.6
Packing Weight (with Fixed Bracket) (kg)/(lbs)	61 / 134.2
Max. Wind Velocity(mph)	150
Mounting hardware	Φ 50 mm ~ Φ 115 mm
Operational Temperature(°C)	-40 to +65
Operational Humidity(%)	<95
Wind Load at 100mph (Frontal/lateral/Rearside(N))	1137/182/852

This publication is issued to information only and is not to form part of any order or contract DENGYO reserves the right to changes specifications without prior notice.

Copyright © 2020 DENGYO All Rights Reserved 2 / 4


BMF6-2LX3HX-CB65 A01

Frequency Range	617-894x2 1695-2690x2 3300-4200
Polarization	±45°
Half-Power Beam Width	65°
Electrical Downtilt	2°-12°x5

Integrated RET Properties


RET Type	4x Type 1 Single RET	
Protocols	Compliant to AISG 2.0/3GPP	
Input voltage range	+10~+30VDC(pin 6)	
Power consumption	<2W(stand by);<13W(motor activated)	
Connectors	AISG	2 x 8 pin connector acc. To IEC 60130-9 Acc.to AISG Daisy chain in:male Daisy chain out:female
	Antenna	Two motor shaft(Embedded motor)
Hardware interface	AISG	RS485A/B(pin5/pin3);Power supply(pin6); DC return(pin7)Acc.to AISG
Adjustment time(full range)	40 sec(typically,depending on antenna)	
Adjustment Cycles	≥10000	
Torque Max	≥160mN.m	
Lightning Protection Rating	IEC 61000-4-5 Current Pulse Profile,8/20 μs 10 Repetitions Min.@ 6kA IEC 61312-1 Annex B Current Pulse Profile, 10/350 μs,200 Repetitions Min. @ 0.6KA	

COMPREHENSIVE TILT CONFIGURATION



Frequency Range	Array	RET Unique ID
617-894MHz	R1/R2	NDPMXXXXXXXX-6089R1
1695-2690MHz	Y1/Y2	NDPMXXXXXXXX-1727Y1
1695-2690MHz	Y3/Y4	NDPMXXXXXXXX-1727Y3
3300-4200MHz	P1	NDPMXXXXXXXX-3342P1


Note: (1) Physical RET Unit containing (4) Single RET



Frequency Range	617-894x2 1695-2690x2 3300-4200
Polarization	$\pm 45^\circ$
Half-Power Beam Width	65°
Electrical Downtilt	2° - $12^\circ \times 5$


Type BMF6-2LX3HX-CB65

Radiation Pattern (617 - 824MHz)




Horizontal Pattern Vertical Pattern

Radiation Patterns (824 - 894 MHz)




Horizontal Pattern Vertical Pattern

Radiation Patterns (1695 - 2170 MHz)




Horizontal Pattern Vertical Pattern

Radiation Patterns (2300 - 2400 MHz)




Horizontal Pattern Vertical Pattern

Radiation Pattern (2490- 2690 MHz)




Horizontal Pattern Vertical Pattern

Radiation Pattern (3300- 4200 MHz)




Horizontal Pattern Vertical Pattern

Radiation Pattern (3300- 4200 MHz)(Service Beam)



Horizontal Pattern Vertical Pattern

Radiation Pattern (3300- 4200 MHz)(Broadcast Beam)



Horizontal Pattern Vertical Pattern